

Description

Hole Diameter: 5/8", MS9276 series washer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS927615
Minimum Qty (MOQ):	10
NSN:	5310-00-085-2933
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N MS9276-15 Specifications

Hole Diameter:	0.570 Inches Minimum And 0.580 Inches Maximum
Outside Diameter:	0.870 Inches Minimum And 0.880 Inches Maximum
External Prebent Key Length:	0.150 Inches Minimum And 0.160 Inches Maximum
External Tapered Key Width:	0.500 Inches Minimum And 0.510 Inches Maximum
External Prebent Key Width:	0.200 Inches Minimum And 0.205 Inches Maximum
Distance From Centerline To Inside Of Prebent Key:	0.540 Inches Minimum And 0.550 Inches Maximum
Overall Distance Including Keys:	1.247 Inches Minimum And 1.280 Inches Maximum
Split Key Length:	0.200 Inches Minimum And 0.205 Inches Maximum
External Key Quantity:	3
Material Thickness:	0.032 Inches Minimum And 0.040 Inches Maximum
Angle Between External Keys:	78.0 Degrees Minimum And 82.0 Degrees Maximum
Special Features:	Both Angular Keys Bent 15.0 Deg Opposite Direction Of Prebent Key
Material:	Steel Comp 321 Overall
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Overall
Style Designator:	Key

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.