

**Description**

Hole Diameter: 5/8", MS9276 series washer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS927616
Minimum Qty (MOQ):	10
NSN:	5310-01-130-3802
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N MS9276-16 Specifications

<b>Hole Diameter:</b>	0.640 Inches Minimum And 0.645 Inches Maximum
<b>Outside Diameter:</b>	0.930 Inches Minimum And 0.940 Inches Maximum
<b>External Prebent Key Length:</b>	0.150 Inches Minimum And 0.160 Inches Maximum
<b>External Tapered Key Width:</b>	0.530 Inches Minimum And 0.540 Inches Maximum
<b>External Prebent Key Width:</b>	0.200 Inches Minimum And 0.205 Inches Maximum
<b>Distance From Centerline To Inside Of Prebent Key:</b>	0.565 Inches Minimum And 0.575 Inches Maximum
<b>Overall Distance Including Keys:</b>	1.290 Inches Nominal
<b>Split Key Length:</b>	0.200 Inches Minimum And 0.205 Inches Maximum
<b>External Key Quantity:</b>	3
<b>Material Thickness:</b>	0.030 Inches Minimum And 0.040 Inches Maximum
<b>Angle Between External Keys:</b>	78.0 Degrees Minimum And 82.0 Degrees Maximum
<b>Material:</b>	Steel Comp 321 Overall
<b>Style Designator:</b>	Key

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.