

Description

Hole Diameter: 1-1/64",

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS927619
Minimum Qty (MOQ):	10
NSN:	5310-01-348-3227
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N MS9276-19 Specifications

Hole Diameter:	1.015 Inches Minimum And 1.020 Inches Maximum
Outside Diameter:	1.430 Inches Minimum And 1.440 Inches Maximum
External Prebent Key Length:	0.150 Inches Minimum And 0.160 Inches Maximum
External Tapered Key Width:	0.650 Inches Minimum And 0.660 Inches Maximum
External Prebent Key Width:	0.290 Inches Minimum And 0.295 Inches Maximum
Distance From Centerline To Inside Of Prebent Key:	0.865 Inches Minimum And 0.875 Inches Maximum
Overall Distance Including Keys:	1.856 Inches Nominal
Split Key Length:	0.235 Inches Nominal
External Key Quantity:	1
Material Thickness:	0.032 Inches Minimum And 0.040 Inches Maximum
Angle Between External Keys:	90.0 Degrees Nominal
External Prebent Key Angle:	15.0 Degrees Nominal
Material:	Steel Comp 321 Overall
Material Document And Classification:	Ams 5510 Assn Std Single Material Response Overall
Style Designator:	Key

How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.