

**Description**

Hole Diameter: 1-1/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS927619
Minimum Qty (MOQ):	10
NSN:	5310-01-348-3227
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



## P/N MS9276-19 Specifications

<b>Hole Diameter:</b>	1.015 Inches Minimum And 1.020 Inches Maximum
<b>Outside Diameter:</b>	1.430 Inches Minimum And 1.440 Inches Maximum
<b>External Prebent Key Length:</b>	0.150 Inches Minimum And 0.160 Inches Maximum
<b>External Tapered Key Width:</b>	0.650 Inches Minimum And 0.660 Inches Maximum
<b>External Prebent Key Width:</b>	0.290 Inches Minimum And 0.295 Inches Maximum
<b>Distance From Centerline To Inside Of Prebent Key:</b>	0.865 Inches Minimum And 0.875 Inches Maximum
<b>Overall Distance Including Keys:</b>	1.856 Inches Nominal
<b>Split Key Length:</b>	0.235 Inches Nominal
<b>External Key Quantity:</b>	1
<b>Material Thickness:</b>	0.032 Inches Minimum And 0.040 Inches Maximum
<b>Angle Between External Keys:</b>	90.0 Degrees Nominal
<b>External Prebent Key Angle:</b>	15.0 Degrees Nominal
<b>Material:</b>	Steel Comp 321 Overall
<b>Material Document And Classification:</b>	Ams 5510 Assn Std Single Material Response Overall
<b>Style Designator:</b>	Key

## How to Order

Order this key washer from our inventory online by visiting <https://military-fasteners.com/washers/key+washers/MS9276-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.