



Military-Fasteners.com

P/N MS9296-28

Description

Fastener Length: 2-1/4", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 15/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS929628
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-090-9065
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9296-28 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.865 Inches Minimum And 0.945 Inches Maximum
Fastener Length:	2.240 Inches Minimum And 2.260 Inches Maximum
Head Style:	Hexagon
Head Height:	0.182 Inches Minimum And 0.198 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.060 Inches Minimum And 0.070 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.315 Inches Minimum And 1.375 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Oxide Overall
Surface Treatment Document And Classification:	Ams 2485 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9296-28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.