

**Description**

Fastener Length: 5/8", Thread: 10-32, Thread Length: 37/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS931605
Minimum Qty (MOQ):	20
NSN:	5305-00-857-2521
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS9316-05 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.573 Inches Minimum And 0.635 Inches Maximum
<b>Fastener Length:</b>	0.615 Inches Minimum And 0.635 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.146 Inches Minimum And 0.166 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum And 36.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel Comp 601
<b>Screw Material Document And Classification:</b>	Ams 6304 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Nickel And Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Ams 2416 Assn Std All Treatment Responses
<b>Thread Series Designator:</b>	Uns

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9316-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.