

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 37/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS931605 |
| Minimum Qty (MOQ): | 20 |
| NSN: | 5305-00-857-2521 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS9316-05 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.573 Inches Minimum And 0.635 Inches Maximum |
| Fastener Length: | 0.615 Inches Minimum And 0.635 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.146 Inches Minimum And 0.166 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 32.0 Rockwell C Minimum And 36.0 Rockwell C Maximum |
| Screw Material: | Steel Comp 601 |
| Screw Material Document And Classification: | Ams 6304 Assn Std Single Material Response |
| Screw Surface Treatment: | Nickel And Cadmium |
| Screw Surface Treatment Document And Classification: | Ams 2416 Assn Std All Treatment Responses |
| Thread Series Designator: | Uns |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9316-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.