

**Description**

Fastener Length: 3/4", Thread: 10-32, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS931607
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-814-4065
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N MS9316-07 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.677 Inches Minimum And 0.695 Inches Maximum
<b>Fastener Length:</b>	0.740 Inches Minimum And 0.760 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.146 Inches Minimum And 0.166 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Internal Drive Style:</b>	Slot
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum And 36.0 Rockwell C Maximum
<b>Screw Material:</b>	Steel Comp 601
<b>Screw Material Document And Classification:</b>	Ams 6304 Assn Std Single Material Response
<b>Screw Surface Treatment:</b>	Nickel And Cadmium
<b>Screw Surface Treatment Document And Classification:</b>	Ams 2416 Assn Std All Treatment Responses
<b>Thread Series Designator:</b>	Uns

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9316-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.