



Military-Fasteners.com

P/N MS9316-08

Description

Fastener Length: 13/16", Thread: 10-32, Thread Length: 39/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS931608
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-081-3728
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc



* See page 2 for technical characteristics

P/N MS9316-08 Specifications

Thread Direction:	Right-hand
Thread Length:	0.604 Inches Minimum And 0.644 Inches Maximum
Fastener Length:	0.802 Inches Minimum And 0.822 Inches Maximum
Head Style:	Hexagon
Head Height:	0.146 Inches Minimum And 0.166 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.190 Inches
Nonstandard Thread Pitch Diameter:	+0.1644/+0.1667 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	32.0 Rockwell C Minimum And 36.0 Rockwell C Maximum
Screw Material:	Steel Comp 601
Screw Material Document And Classification:	Ams 6304 Assn Std Single Material Response
Screw Surface Treatment:	Nickel And Cadmium
Screw Surface Treatment Document And Classification:	Ams 2416 Assn Std All Treatment Responses
Thread Series Designator:	Uns

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9316-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.