

Description

Fastener Length: 0-1/1", Thread: 10-32, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-------------------------------|
| SKU / Model: | MS931611 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-852-4233 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N MS9316-11 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.677 Inches Minimum And 0.695 Inches Maximum |
| Fastener Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.146 Inches Minimum And 0.166 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Internal Drive Style: | Slot |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 32.0 Rockwell C Minimum And 36.0 Rockwell C Maximum |
| Screw Material: | Steel Comp 601 |
| Screw Material Document And Classification: | Ams 6304 Assn Std Single Material Response |
| Screw Surface Treatment: | Nickel And Cadmium |
| Screw Surface Treatment Document And Classification: | Ams 2416 Assn Std All Treatment Responses |
| Thread Series Designator: | Uns |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9316-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.