



Military-Fasteners.com

P/N MS9316-13

Description

Fastener Length: 1-1/8", Thread: 10-32, Thread Length: 5/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS931613
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-857-3367
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9316-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.615 Inches Minimum And 0.757 Inches Maximum
Fastener Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Head Style:	Hexagon
Head Height:	0.146 Inches Minimum And 0.166 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Hardness Rating:	32.0 Rockwell C Minimum And 36.0 Rockwell C Maximum
Screw Material:	Steel Comp 601
Screw Material Document And Classification:	Ams 6304 Assn Std Single Material Response
Screw Surface Treatment:	Nickel And Cadmium
Screw Surface Treatment Document And Classification:	Ams 2416 Assn Std All Treatment Responses
Thread Series Designator:	Uns

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9316-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.