

Description

MS9318-058 Rivet

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS9318058
Minimum Qty (MOQ):	100
NSN:	5320-00-121-8449
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE
AVAILABLE

P/N MS9318-058 Specifications

Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Flush (flat) Countersunk (included Angle - Less Than 135 Deg W Or W/o Chamfer)
Shank Diameter:	0.093 Inches Minimum And 0.095 Inches Maximum
Shank Style:	Straight
Head Major Diameter:	0.164 Inches Minimum And 0.172 Inches Maximum
Shear Strength:	49000 Single Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Heat Treatment:	Annealed Overall
Material:	Steel Corrosion Resisting Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS9318-058> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.