

Description

MS9403-070 Solid Rivet

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS9403070
Minimum Qty (MOQ):	100
NSN:	5320-01-097-9983
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



* See page 2 for technical characteristics

P/N MS9403-070 Specifications

Fastener Length:	0.344 Inches Nominal
Head Style:	Universal
Head Height:	0.040 Inches Minimum And 0.050 Inches Maximum
Shank Diameter:	0.093 Inches Minimum And 0.095 Inches Maximum
Shank Style:	Countersunk (undrilled)
Head Major Diameter:	0.179 Inches Minimum And 0.197 Inches Maximum
Shear Strength:	80000 Single Pounds Per Square Inch
Heat Treatment:	Solution Heat Treated Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall

How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS9403-070> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.