

**Description**

MS9403-070 Solid Rivet

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS9403070
Minimum Qty (MOQ):	100
NSN:	5320-01-097-9983
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc



NO IMAGE  
AVAILABLE

## P/N MS9403-070 Specifications

<b>Fastener Length:</b>	0.344 Inches Nominal
<b>Head Style:</b>	Universal
<b>Head Height:</b>	0.040 Inches Minimum And 0.050 Inches Maximum
<b>Shank Diameter:</b>	0.093 Inches Minimum And 0.095 Inches Maximum
<b>Shank Style:</b>	Countersunk (undrilled)
<b>Head Major Diameter:</b>	0.179 Inches Minimum And 0.197 Inches Maximum
<b>Shear Strength:</b>	80000 Single Pounds Per Square Inch
<b>Heat Treatment:</b>	Solution Heat Treated Overall
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall

## How to Order

Order this solid rivet from our inventory online by visiting <https://military-fasteners.com/rivets/solid+rivets/MS9403-070> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.