

Description

length: 7/16", thread: 10-32, tee head, chamfered, MS9432 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS943205
Minimum Qty (MOQ):	5
NSN:	5306-00-947-3541
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9432-05 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.294 Inches Minimum And 0.334 Inches Maximum
Fastener Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Head Style:	Tee No. 6
Head Height:	0.115 Inches Minimum And 0.135 Inches Maximum
Head Length:	0.420 Inches Minimum And 0.440 Inches Maximum
Width Between Flats:	0.310 Inches Minimum And 0.320 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Chamfer Angle:	45.0 Degrees Minimum And 47.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this tee head bolt from our inventory online by visiting <https://military-fasteners.com/bolts/tee+head+bolts/MS9432-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.