

Description

length: 7/16", thread: 10-32, tee head, chamfered, MS9432 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS943205 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-00-947-3541 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS9432-05 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.294 Inches Minimum And 0.334 Inches Maximum |
| Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Head Style: | Tee No. 6 |
| Head Height: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Head Length: | 0.420 Inches Minimum And 0.440 Inches Maximum |
| Width Between Flats: | 0.310 Inches Minimum And 0.320 Inches Maximum |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Yield Strength: | 85000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Threads |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 63.0 Microinches Grip |
| Chamfer Angle: | 45.0 Degrees Minimum And 47.0 Degrees Maximum |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5735 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this tee head bolt from our inventory online by visiting <https://military-fasteners.com/bolts/tee+head+bolts/MS9432-05> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.