

**Description**

length: 9/16", thread: 10-32, tee head bolt - chamfered"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS943207
Minimum Qty (MOQ):	5
NSN:	5306-01-177-0867
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS9432-07 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.418 Inches Minimum And 0.458 Inches Maximum
<b>Fastener Length:</b>	0.552 Inches Minimum And 0.572 Inches Maximum
<b>Head Style:</b>	Tee No. 6
<b>Head Height:</b>	0.115 Inches Minimum And 0.135 Inches Maximum
<b>Head Length:</b>	0.420 Inches Minimum And 0.440 Inches Maximum
<b>Width Between Flats:</b>	0.310 Inches Minimum And 0.320 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	85000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	63.0 Microinches Grip
<b>Chamfer Angle:</b>	45.0 Degrees Minimum And 47.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5732 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this tee head bolt from our inventory online by visiting <https://military-fasteners.com/bolts/tee+head+bolts/MS9432-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.