

Description

Fastener Length: 11/16", Thread: 10-32, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS943209
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-432-4674
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	013280, Alum Bolts



* See page 2 for technical characteristics

P/N MS9432-09 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.554 Inches Minimum And 0.574 Inches Maximum
Fastener Length:	0.688 Inches Nominal
Head Style:	Tee No. 6
Head Height:	0.125 Inches Nominal
Head Length:	0.420 Inches Minimum And 0.440 Inches Maximum
Width Between Flats:	0.310 Inches Minimum And 0.320 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Chamfer Angle:	45.0 Degrees Minimum And 47.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/tee+head+bolts/MS9432-09> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.