

## P/N MS9432-11

### **Description**

Fastener Length: 3/4", Thread: 10-32, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS943	211
Minimum Qty (MOQ): 5 EA	
NSN: 5306-	00-508-2068

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS9432-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.630 Inches Minimum And 0.690 Inches Maximum
Fastener Length:	0.812 Inches Nominal
Head Style:	Tee No. 6
Head Height:	0.125 Inches Nominal
Head Length:	0.420 Inches Minimum And 0.440 Inches Maximum
Width Between Flats:	0.310 Inches Minimum And 0.320 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Chamfer Angle:	45.0 Degrees Minimum And 47.0 Degrees Maximum
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5735 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/tee+head+bolts/MS9432-11">https://military-fasteners.com/bolts/tee+head+bolts/MS9432-11</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.