



Military-Fasteners.com

P/N MS9432-11

## Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS943211
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-508-2068
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS9432-11 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.630 Inches Minimum And 0.690 Inches Maximum
<b>Fastener Length:</b>	0.812 Inches Nominal
<b>Head Style:</b>	Tee No. 6
<b>Head Height:</b>	0.125 Inches Nominal
<b>Head Length:</b>	0.420 Inches Minimum And 0.440 Inches Maximum
<b>Width Between Flats:</b>	0.310 Inches Minimum And 0.320 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	85000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Surface Finish:</b>	63.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	63.0 Microinches Grip
<b>Chamfer Angle:</b>	45.0 Degrees Minimum And 47.0 Degrees Maximum
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5735 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/tee+head+bolts/MS9432-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.