

Description

Fastener Length: 1/2", Hole Diameter: ", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS944106 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-943-2106 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS9441-06 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.401 Inches Minimum And 0.421 Inches Maximum |
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.250 Inches Nominal |
| Width Between Flats: | 0.430 Inches Minimum And 0.439 Inches Maximum |
| Hole Diameter: | 0.060 Inches Nominal |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.079 Inches Minimum And 0.099 Inches Maximum |
| Hole Quantity: | 6 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Hardness Rating: | 42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Longitudinal Hole |
| Material: | Steel Comp 601 Overall |
| Material Document And Classification: | Ams 6304 Assn Std Single Material Response Overall |
| Surface Treatment: | Nickel Overall And Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9441-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.