

Description

Fastener Length: 1/2", Thread: 1/4-28, Thread Length: 13/32

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS945206
Minimum Qty (MOQ):	2
NSN:	5306-01-327-3525
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9452-06 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.411 Inches Nominal
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Hexagon
Head Height:	0.146 Inches Minimum And 0.166 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 601 Overall
Material Document And Classification:	Ams 6304 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9452-06> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.