

Description

Fastener Length: 0-63/64", Thread: 1/4-24, Thread Length: 7/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS945312
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-145-5439
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9453-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.845 Inches Minimum And 0.885 Inches Maximum
Fastener Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Head Style:	Hexagon
Head Height:	0.188 Inches Nominal
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.125 Inches Minimum And 0.145 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Comp 601 Overall
Material Document And Classification:	Ams6304 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall
Surface Treatment Document And Classification:	Ams2416 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9453-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.