

Description

Fastener Length: 0-63/64", Thread: 3/8-24, Thread Length: 59/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS945410
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-118-9556
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9454-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.882 Inches Minimum And 0.922 Inches Maximum
Fastener Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Head Style:	Hexagon
Head Height:	0.209 Inches Minimum And 0.229 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.088 Inches Minimum And 0.108 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hardness Rating:	42.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Surface Finish:	63.0 Microinches Grip
Material:	Steel Overall
Material Document And Classification:	Ams6304 Assn Std Single Material Response Overall
Surface Treatment:	Nickel Overall And Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Ams2416 Assn Std All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9454-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.