

P/N MS9487-12

Description

Fastener Length: 7/8", Thread: 6-40, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: MS948712
Minimum Qty (MOQ): 5 EA

NSN: 5305-01-127-7076

Schedule B: 7318.15.6080

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS9487-12 Specifications

| Thread Class: | 3a |
|---------------------------------------------|-----------------------------------------------------|
| Thread Direction: | Right-hand |
| Thread Length: | 0.516 Inches Minimum And 0.596 Inches Maximum |
| Fastener Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.094 Inches Minimum And 0.106 Inches Maximum |
| Width Between Flats: | 0.243 Inches Minimum And 0.251 Inches Maximum |
| Nominal Thread Diameter: | 0.138 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 130000 Pounds Per Square Inch |
| Hardness Rating: | 24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum |
| Screw Material: | Iron Alloy 660 |
| Screw Material Document And Classification: | Ams5731 Assn Std Single Material Response |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS9487-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS9487-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS9487-12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms9487-12 and selecting the quantity you want then