



Military-Fasteners.com

P/N MS9487-12

Description

Fastener Length: 7/8", Thread: 6-40, Thread Length: 33/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS948712
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-127-7076
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9487-12 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.516 Inches Minimum And 0.596 Inches Maximum
Fastener Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Head Style:	Hexagon
Head Height:	0.094 Inches Minimum And 0.106 Inches Maximum
Width Between Flats:	0.243 Inches Minimum And 0.251 Inches Maximum
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
Screw Material:	Iron Alloy 660
Screw Material Document And Classification:	Ams5731 Assn Std Single Material Response
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9487-12> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.