

**Description**

Fastener Length: 5/16", Thread: 8-36, Thread Length: 15/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS948803
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-126-7311
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS9488-03 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.220 Inches Minimum And 0.260 Inches Maximum
<b>Fastener Length:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.106 Inches Minimum And 0.118 Inches Maximum
<b>Width Between Flats:</b>	0.305 Inches Minimum And 0.313 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	36
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	24.0 Rockwell C Minimum And 35.0 Rockwell C Maximum
<b>Screw Material:</b>	Iron Alloy 660
<b>Screw Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9488-03> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.