

## P/N MS9488-08

### **Description**

Fastener Length: 5/8", Thread: 8-36, Thread Length: 31/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

 SKU / Model:
 MS948808

 Minimum Qty (MOQ):
 5 EA

 NSN:
 5306-01-394-6806

 Schedule B:
 7318,15,6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS9488-08 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.470 Inches Minimum And 0.510 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Hexagon
Head Height:	0.106 Inches Minimum And 0.118 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.062 Inches Minimum And 0.082 Inches Maximum
Thread Quantity Per Inch:	36
Material:	Iron Alloy 660 Overall
Thread Series Designator:	Unjf

# **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS9488-08">https://military-fasteners.com/screws/machine+screws/MS9488-08</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS9488-08">https://military-fasteners.com/screws/machine+screws/MS9488-08</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/MS9488-08">https://military-fasteners.com/screws/machine+screws/MS9488-08</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/machine+screws/ms9488-08">https://military-fasteners.com/screws/ms9488-08</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/ms9488-08">https://military-fasteners.com/screws/ms9488-08</a> and selecting the property of the proper