

P/N MS9489-17

Military-Fasteners.com

#### Description

Fastener Length: 1-3/16", Thread: 10-32, Thread Length: 11/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	MS948917
Minimum Qty (MOQ):	10 EA
NSN:	5306-00-146-2627
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



# P/N MS9489-17 Specifications

Thread Class:3aThread Direction:Night-handThread Length:0.630 Inches Minimum And 0.690 Inches MaximumFastener Length:0.630 Inches Minimum And 0.690 Inches MaximumHead Style:HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.367 Inches Minimum And 0.376 Inches MaximumGrip Length:0.498 Inches Minimum And 0.558 Inches MaximumFeatres Provided:Finished HeadThread Quartity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:24.0 Miroinches Bazing Surface Of HeadSurface Finish:32.0 Microinches Bazing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Thread Surface Of HeadMaterial Document And Classification:Most Syla Syla Sila Sila Sila Sila Sila Sila Sila Si		
Thread Length:0.630 Inches Minimum And 0.690 Inches MaximumFastener Length:1.188 Inches NominalHead Style:HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.498 Inches Minimum And 0.558 Inches MaximumFeatures Provided:Finishe HeadThread Quantity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:85000 Pounds Per Square InchMinimum Yield Strength:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Iron Alloy 660 OverallMaterial:Iron Alloy 660 Overall	Thread Class:	3a
Fastener Length:1.88 Inches NominalHead Style:HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.498 Inches Minimum And 0.558 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Inon Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Thread Direction:	Right-hand
Head Style:HexagonHead Height:0.125 Inches NominalWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.498 Inches Minimum And 0.558 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Iron Alloy 660 OverallMaterial:Kon S731 Assn Std Single Material Response Overall	Thread Length:	0.630 Inches Minimum And 0.690 Inches Maximum
Head Height:0.125 Inches NominalWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.498 Inches Minimum And 0.558 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Fastener Length:	1.188 Inches Nominal
Width Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.498 Inches Minimum And 0.558 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Ino Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Head Style:	Hexagon
Nominal Thread Diameter:0.190 InchesGrip Length:0.498 Inches Minimum And 0.558 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Head Height:	0.125 Inches Nominal
Grip Length:0.498 Inches Minimum And 0.558 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Features Provided:Finished HeadFread Quantity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:32Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Grip Length:	0.498 Inches Minimum And 0.558 Inches Maximum
Minimum Tensile Strength:130000 Pounds Per Square InchHardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Features Provided:	Finished Head
Hardness Rating:248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum OverallMinimum Yield Strength:85000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Thread Quantity Per Inch:	32
Minimum Yield Strength:85000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Minimum Tensile Strength:	130000 Pounds Per Square Inch
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams 5731 Assn Std Single Material Response Overall	Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish: 32.0 Microinches Threads   Material: Iron Alloy 660 Overall   Material Document And Classification: Ams 5731 Assn Std Single Material Response Overall	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Iron Alloy 660 Overall   Material Document And Classification: Ams 5731 Assn Std Single Material Response Overall	Surface Finish:	32.0 Microinches Grip
Material Document And Classification:   Ams 5731 Assn Std Single Material Response Overall	Surface Finish:	32.0 Microinches Threads
	Material:	Iron Alloy 660 Overall
Thread Series Designator: Unjf	Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
	Thread Series Designator:	Unjf

## How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS9489-17</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.