

Description

Fastener Length: 3-1/2", Thread: 10-32, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS948940
Minimum Qty (MOQ):	5 EA
NSN:	5306-00-083-5204
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9489-40 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.620 Inches Minimum And 0.700 Inches Maximum
Fastener Length:	3.490 Inches Minimum And 3.510 Inches Maximum
Head Style:	Hexagon
Head Height:	0.115 Inches Minimum And 0.135 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	2.810 Inches Minimum And 2.870 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9489-40> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.