

Description

Fastener Length: 1-3/8", Thread: 1/4-28, Thread Length: 51/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS949020
Minimum Qty (MOQ):	10
NSN:	5306-01-282-8984
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9490-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.750 Inches Minimum And 0.810 Inches Maximum
Fastener Length:	1.375 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
End Item Identification:	Gas Generator Assembly Mdl L25250g12
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9490-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.