

P/N MS9491-06

Description

SKIL / Model

Fastener Length: 5/8", Thread: 1/4-24, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: M39491	70
Minimum Qty (MOQ): 5 EA	
NSN: 5306-00	406-0779
Schedule B: 7318.15	8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)

MC040106



^{*} See page 2 for technical characteristics

P/N MS9491-06 Specifications

3a
Right-hand
0.517 Inches Minimum And 0.537 Inches Maximum
0.625 Inches Nominal
Hexagon
0.188 Inches Nominal
0.492 Inches Minimum And 0.502 Inches Maximum
0.312 Inches
0.088 Inches Minimum And 0.108 Inches Maximum
Finished Head
24
130000 Pounds Per Square Inch
248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
85000 Pounds Per Square Inch
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Iron Alloy 660 Overall
Ams 5731 Assn Std Single Material Response Overall
Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9491-06 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.