

P/N MS9492-05

Military-Fasteners.com

Description

Fastener Length: 11/16", Thread: 3/8-24, Thread Length: 37/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS949205
Minimum Qty (MOQ):	1
NSN:	5306-01-108-3179
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS9492-05 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.570 Inches Minimum And 0.610 Inches Maximum
Fastener Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Head Style:	Hexagon
Head Height:	0.209 Inches Minimum And 0.229 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.088 Inches Minimum And 0.188 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS9492-05</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.