

Description

Fastener Length: 1-3/16", Thread: 3/8-24, Thread Length: 0-1/1"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS949213
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-529-6588
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N MS9492-13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.990 Inches Minimum And 1.070 Inches Maximum
Fastener Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Head Style:	Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.128 Inches Minimum And 0.188 Inches Maximum
Thread Quantity Per Inch:	24
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine - hexagon head bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9492-13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.