

P/N MS9494-26

Description

Fastener Length: 2-5/8", Thread: 1/2-20, Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	MS949426
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-136-2728
Schedule B:	7318.15.8085
ECCN:	9A991



^{*} See page 2 for technical characteristics

P/N MS9494-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.250 Inches Minimum And 1.310 Inches Maximum
Fastener Length:	2.625 Inches Nominal
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.315 Inches Minimum And 1.375 Inches Maximum
Features Provided:	Finished Head
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Material:	Iron Alloy Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	96906-ms9494 Government Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9494-26 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.