



MILITARY ★ FASTENERS

Military-Fasteners.com

P/N MS9500-07

Description

Fastener Length: 1/2", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 31/64", MS9500 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS950007
Minimum Qty (MOQ):	5
NSN:	5306-00-571-9570
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS9500-07 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.470 Inches Minimum And 0.490 Inches Maximum
Fastener Length:	0.562 Inches Nominal
Head Style:	Hexagon
Head Height:	0.134 Inches Minimum And 0.150 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.047 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.072 Inches Minimum And 0.092 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	130000 Pounds Per Square Inch
Hardness Rating:	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
Minimum Yield Strength:	85000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Flats
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9500-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.