

**Description**

Fastener Length: 1/2", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 31/64", MS9500 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS950007
Minimum Qty (MOQ):	5
NSN:	5306-00-571-9570
Schedule B:	7318.15.2000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS9500-07 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.470 Inches Minimum And 0.490 Inches Maximum
<b>Fastener Length:</b>	0.562 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.134 Inches Minimum And 0.150 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Hole Diameter:</b>	0.047 Inches Nominal
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	0.072 Inches Minimum And 0.092 Inches Maximum
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	130000 Pounds Per Square Inch
<b>Hardness Rating:</b>	24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall
<b>Minimum Yield Strength:</b>	85000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Hexagon Flats
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9500-07> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.