

Description

Fastener Length: 1-7/16", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS950021 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-00-781-7872 |
| Schedule B: | 7318.15.2010 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS9500-21 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.630 Inches Minimum And 0.690 Inches Maximum |
| Fastener Length: | 1.438 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.134 Inches Minimum And 0.150 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Hole Diameter: | 0.042 Inches Nominal |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.748 Inches Minimum And 0.808 Inches Maximum |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 130000 Pounds Per Square Inch |
| Hardness Rating: | 248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall |
| Minimum Yield Strength: | 85000 Pounds Per Square Inch |
| Hole Configuration Style: | Hexagon Flats |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5731 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9500-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.