

P/N MS9502-04

Description

Fastener Length: 1/2", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS950204
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-434-6985
Schedule B:	7318.15.8085
FCCN:	FAR99



^{*} See page 2 for technical characteristics

P/N MS9502-04 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.392 Inches Minimum And 0.412 Inches Maximum
Fastener Length:	0.500 Inches Nominal
Head Style:	Hexagon
Head Height:	0.182 Inches Minimum And 0.198 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.060 Inches Minimum And 0.070 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.088 Inches Minimum And 0.108 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Hole Configuration Style:	Hexagon Flats
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/MS9502-04 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.