

Description

Fastener Length: 1/2", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | MS950204 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-434-6985 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N MS9502-04 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.392 Inches Minimum And 0.412 Inches Maximum |
| Fastener Length: | 0.500 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.182 Inches Minimum And 0.198 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Hole Diameter: | 0.060 Inches Minimum And 0.070 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.088 Inches Minimum And 0.108 Inches Maximum |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 24 |
| Hole Configuration Style: | Hexagon Flats |
| Material: | Steel Corrosion Resisting Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9502-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.