



Military-Fasteners.com

P/N MS9502-08

## Description

Fastener Length: 3/4", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 43/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS950208                                  |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-01-159-9388                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS9502-08 Specifications

|  |   |
|--|---|
| <b>Thread Class:</b>                         | 3a  |
| <b>Thread Direction:</b>                     | Right-hand  |
| <b>Thread Length:</b>                        | 0.632 Inches Minimum And 0.672 Inches Maximum                       |
| <b>Fastener Length:</b>                      | 0.740 Inches Minimum And 0.760 Inches Maximum                       |
| <b>Head Style:</b>                           | Hexagon   |
| <b>Head Height:</b>                          | 0.182 Inches Minimum And 0.198 Inches Maximum                       |
| <b>Width Between Flats:</b>                  | 0.492 Inches Minimum And 0.502 Inches Maximum                       |
| <b>Hole Diameter:</b>                        | 0.060 Inches Minimum And 0.070 Inches Maximum                       |
| <b>Nominal Thread Diameter:</b>              | 0.312 Inches  |
| <b>Grip Length:</b>                          | 0.088 Inches Minimum And 0.108 Inches Maximum                       |
| <b>Hole Quantity:</b>                        | 1   |
| <b>Hole Type:</b>                            | Drilled   |
| <b>Features Provided:</b>                    | Finished Head   |
| <b>Thread Quantity Per Inch:</b>             | 24  |
| <b>Minimum Tensile Strength:</b>             | 130000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                      | 24.0 Rockwell C Minimum Overall And 35.0 Rockwell C Maximum Overall |
| <b>Minimum Yield Strength:</b>               | 85000 Pounds Per Square Inch  |
| <b>Hole Configuration Style:</b>             | Hexagon Flats   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads  |
| <b>Material:</b>                             | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b> | Ams 5731 Assn Std Single Material Response Overall                  |
| <b>Thread Series Designator:</b>             | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9502-08> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.