

Description

Fastener Length: 1-63/64", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 59/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS950226
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-278-1956
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N MS9502-26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.875 Inches Minimum And 0.935 Inches Maximum
Fastener Length:	1.990 Inches Minimum And 2.010 Inches Maximum
Head Style:	Hexagon
Head Height:	0.182 Inches Minimum And 0.198 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.060 Inches Minimum And 0.070 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.065 Inches Minimum And 1.125 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hole Configuration Style:	Hexagon Flats
Surface Finish:	125.0 Microinches Grip
Surface Finish:	125.0 Microinches Sides Of Head
Surface Finish:	125.0 Microinches Top Of Head
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Uns S66286 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	96906-ms9502 Government Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9502-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.