

Description

Fastener Length: 1-63/64", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 59/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS950226
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-278-1956
Schedule B:	7318.15.8085
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N MS9502-26 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.875 Inches Minimum And 0.935 Inches Maximum
<b>Fastener Length:</b>	1.990 Inches Minimum And 2.010 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.182 Inches Minimum And 0.198 Inches Maximum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.502 Inches Maximum
<b>Hole Diameter:</b>	0.060 Inches Minimum And 0.070 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.065 Inches Minimum And 1.125 Inches Maximum
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Features Provided:</b>	Finished Head
<b>Thread Quantity Per Inch:</b>	24
<b>Hole Configuration Style:</b>	Hexagon Flats
<b>Surface Finish:</b>	125.0 Microinches Grip
<b>Surface Finish:</b>	125.0 Microinches Sides Of Head
<b>Surface Finish:</b>	125.0 Microinches Top Of Head
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5731 Uns S66286 Assn Std Single Material Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	96906-ms9502 Government Standard

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9502-26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.