



Military-Fasteners.com

P/N MS9503-04

Description

Fastener Length: 5/8", Hole Diameter: 1/16", Thread: 3/8-24, Thread Length: 17/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS950304
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-478-0332
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi Sub 9



* See page 2 for technical characteristics

P/N MS9503-04 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.517 Inches Minimum And 0.537 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Hexagon
Head Height:	0.219 Inches Nominal
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Hole Diameter:	0.065 Inches Nominal
Nominal Thread Diameter:	0.375 Inches
Grip Length:	0.088 Inches Minimum And 0.108 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Hardness Rating:	248.0 Brinell Standard Minimum Overall And 341.0 Brinell Standard Maximum Overall
Hole Configuration Style:	Hexagon Flats
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9503-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.