

Description

Fastener Length: 2-1/2", Hole Diameter: 5/64", Thread: 1/2-20, Thread Length: 1-9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS950525
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-514-1898
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS9505-25 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.280 Inches Nominal
Fastener Length:	2.500 Inches Nominal
Head Style:	Hexagon
Head Height:	0.281 Inches Nominal
Width Between Flats:	0.741 Inches Minimum And 0.752 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Grip Diameter:	0.495 Inches Minimum And 0.499 Inches Maximum
End Item Identification:	Lube S&c System
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.190 Inches Minimum And 1.250 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9505-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.