

Description

externally

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS951704
Minimum Qty (MOQ):	10
NSN:	5305-01-420-9833
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



P/N MS9517-04 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.293 Inches Minimum And 0.313 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Hexagon
Head Height:	0.106 Inches Minimum And 0.118 Inches Maximum
Width Between Flats:	0.305 Inches Minimum And 0.313 Inches Maximum
First Diameter From Head:	0.141 Inches Minimum And 0.151 Inches Maximum
Distance From Largest Bearing Surface Of Head To End Of First Diameter:	0.062 Inches Minimum And 0.082 Inches Maximum
Internal Drive Style:	W/o Internal Drive
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	36
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Externally Relieved Body Diameter Quantity:	1
Material:	Steel Comp 8740 Overall
Material Document And Classification:	Ams 6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams 2400 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9517-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.