

**Description**

externally

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS951704
Minimum Qty (MOQ):	10
NSN:	5305-01-420-9833
ECCN:	EAR99
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



## P/N MS9517-04 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.293 Inches Minimum And 0.313 Inches Maximum
<b>Fastener Length:</b>	0.375 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.106 Inches Minimum And 0.118 Inches Maximum
<b>Width Between Flats:</b>	0.305 Inches Minimum And 0.313 Inches Maximum
<b>First Diameter From Head:</b>	0.141 Inches Minimum And 0.151 Inches Maximum
<b>Distance From Largest Bearing Surface Of Head To End Of First Diameter:</b>	0.062 Inches Minimum And 0.082 Inches Maximum
<b>Internal Drive Style:</b>	W/o Internal Drive
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	36
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Externally Relieved Body Diameter Quantity:</b>	1
<b>Material:</b>	Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams 6322 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams 2400 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS9517-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.