

P/N MS9518-05

Military-Fasteners.com

Description

Fastener Length: 7/16", Thread: 10-32, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS951805 |
|-------------------------|---|
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-157-3365 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS9518-05 Specifications

| Thread Direction:Right-handThread Length:0.336 Inches Minimum And 0.376 Inches MaximumFastener Length:0.428 Inches Minimum And 0.448 Inches MaximumHead Style:HexagonHead Style:0.151 Inches Minimum And 0.135 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.367 Inches Minimum And 0.376 Inches MaximumGrip Length:0.190 InchesFatures Provided:N172 Inches Minimum And 0.092 Inches MaximumThread Quantity Per Inch:32Surface Finish:20.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:Seel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Asn Std Single Material Response OverallSurface Treatment:Comium OverallSurface Treatment Response OverallMicroinches Grip | | _ |
|---|--|---|
| Thread Length:0.336 Inches Minimum And 0.376 Inches MaximumFastener Length:0.428 Inches Minimum And 0.448 Inches MaximumHead Style:HexagonHead Height:0.115 Inches Minimum And 0.135 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.367 Inches Minimum And 0.092 Inches MaximumGrip Length:0.190 InchesFeatures Provided:Finished HeadThread Quantity Per Inch:32.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Thread Class: | За |
| Fastener Length:0.428 Inches Minimum And 0.448 Inches MaximumHead Style:HexagonHead Height:0.115 Inches Minimum And 0.135 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.072 Inches Minimum And 0.092 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Surface Finish:0.010 cinches Bearing Surface Of HeadSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Thread Direction: | Right-hand |
| Head Style:HexagonHead Height:0.115 Inches Minimum And 0.135 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.072 Inches Minimum And 0.092 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Thread Length: | 0.336 Inches Minimum And 0.376 Inches Maximum |
| Head Height:0.115 Inches Minimum And 0.135 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.072 Inches Minimum And 0.092 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Bardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSurface Finish:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Fastener Length: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Width Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.772 Inches Minimum And 0.092 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Bardness Rating:6.0.80 Kowell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripBaterial:Stel Comp 8740 OverallMaterial:Mission Surface Surfa | Head Style: | Hexagon |
| Nominal Thread Diameter:0.190 InchesGrip Length:0.072 Inches Minimum And 0.092 Inches MaximumFeatures Provided:Finished HeadThread Quantity Per Inch:32Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium Overall | Head Height: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Grip Length:0.072 Inches Minimum And 0.092 Inches MaximumFeatures Provided:Finished HeadFread Quantity Per Inch:32Hardness Rating:6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Surface Statigication:Material Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Material: | Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Features Provided:Finished HeadFeatures Provided:Finished HeadThread Quantity Per Inch:32Hardness Rating:Co. Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Codmium OverallSurface Treatment And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch:32Hardness Rating:32Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Grip Length: | 0.072 Inches Minimum And 0.092 Inches Maximum |
| Hardness Rating:26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum OverallSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Features Provided: | Finished Head |
| Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Mate 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallMaterial:Material Steel Comp 8740 Single Material Response OverallSurface Treatment:Surface Treatment Response OverallSurface Treatment:Material Single Material Response OverallSurface Treatment:Material Single Treatment Response Overall | Thread Quantity Per Inch: | 32 |
| Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Surface Finish:32.0 Microinches ThreadsMaterial:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Material:Steel Comp 8740 OverallMaterial Document And Classification:Ams 6322 Assn Std Single Material Response OverallSurface Treatment:Cadmium OverallSurface Treatment Document And Classification:Ams 2400 Assn Std Single Treatment Response Overall | Surface Finish: | 32.0 Microinches Grip |
| Material Document And Classification: Ams 6322 Assn Std Single Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Ams 2400 Assn Std Single Treatment Response Overall | Surface Finish: | 32.0 Microinches Threads |
| Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Ams 2400 Assn Std Single Treatment Response Overall | Material: | Steel Comp 8740 Overall |
| Surface Treatment Document And Classification: Ams 2400 Assn Std Single Treatment Response Overall | Material Document And Classification: | Ams 6322 Assn Std Single Material Response Overall |
| | Surface Treatment: | Cadmium Overall |
| Thread Series Designator: Unjf | Surface Treatment Document And Classification: | Ams 2400 Assn Std Single Treatment Response Overall |
| | Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/MS9518-05</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.