

**Description**

Fastener Length: 2-1/2", Thread: 10-32, Thread Length: 11/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS951832
Minimum Qty (MOQ):	20
NSN:	5306-01-548-3073
Schedule B:	7318.15.8085
ECCN:	EAR99



## P/N MS9518-32 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.690 Inches Nominal
<b>Fastener Length:</b>	2.500 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.125 Inches Nominal
<b>Width Between Flats:</b>	0.419 Inches Nominal
<b>Grip Diameter:</b>	0.165 Inches Minimum And 0.175 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	1.810 Inches Minimum And 1.870 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Material Document And Classification:</b>	Ams6322-80 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Ams2400-80 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9518-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.