

Description

Fastener Length: 3/8", Thread: 1/4-32, Thread Length: 9/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS951904
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-548-3080
Schedule B:	7318.15.2010
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N MS9519-04 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.276 Inches Minimum And 0.296 Inches Maximum
Fastener Length:	0.375 Inches Nominal
Head Style:	Hexagon
Head Height:	0.156 Inches Nominal
Width Between Flats:	0.491 Inches Nominal
Grip Diameter:	0.222 Inches Minimum And 0.232 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.079 Inches Minimum And 0.099 Inches Maximum
Thread Quantity Per Inch:	32
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Material:	Steel Overall
Material Document And Classification:	Ams6322-80 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams2400-80 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/MS9519-04> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.